

|                |                              |
|----------------|------------------------------|
| <b>Product</b> | LivePremier Simulator        |
| <b>Date</b>    | July 30 <sup>th</sup> , 2020 |
| <b>Version</b> | 1.1.8                        |

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

---

## Technical Notes:

---

### **Warning when simulating LivePremier firmware v2.0.228:**

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

### New Feature

- Simulation of LivePremier firmware v2.0.228
- Generation of ordering numbers for LivePremier's Aquilon C and C+

### Evolution

- None.

### Bug fixes

- None

# PREVIOUS VERSIONS

|                |                             |
|----------------|-----------------------------|
| <b>Product</b> | LivePremier Simulator       |
| <b>Date</b>    | May 18 <sup>th</sup> , 2020 |
| <b>Version</b> | 1.0.6                       |

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

---

## **Technical Notes:**

---

### New Feature

- The LivePremier Simulator is now also available for Mac.

### Evolution

- None.

### Bug fixes

- Working with RC400T can crash the Web RCS server
- Correction on AOI management
- Output capacities may be inconsistent

|                |                               |
|----------------|-------------------------------|
| <b>Product</b> | LivePremier Simulator         |
| <b>Date</b>    | April 29 <sup>th</sup> , 2020 |
| <b>Version</b> | 1.00.00                       |

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

---

## Technical Notes:

---

### Supported OS

This initial version is only available for Microsoft Windows systems. The Mac OS version will be released later.

### Initial published release

- Support for LivePremier series: Aquilon RS alpha, RS1, RS2, RS3, RS4, C and C+
- Simulation of LivePremier firmware v1.2.10
- Customizable I/O card types
- Up to 10 session slots, one session running at a time
- 2 possible input formats depending on input capacity:
  - o Capacity 1: 1920x 1080
  - o Capacity 2: 3840x 2160
- Import/Export of the device configuration using the Web RCS
- Usable with RC400T