

<b>Product</b>	LivePremier Simulator
<b>Date</b>	November 29 <sup>th</sup> , 2022
<b>Version</b>	2.0.6

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Warnings

- **do not use LivePremier Simulator and Midra 4K Simulator simultaneously as erroneous behaviors may be encountered.**
- **when simulating LivePremier firmware v2.0.228 and above:**
  - **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
  - **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

### New Feature

- Supports LivePremier firmware v3.0.255

### Evolution

- Interface update

### Bug fixes

- None

# PREVIOUS VERSIONS

<b>Product</b>	LivePremier Simulator
<b>Date</b>	April 19 <sup>th</sup> , 2022
<b>Version</b>	1.6.1

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Warnings

- **do not use LivePremier Simulator and Midra 4K Simulator simultaneously as erroneous behaviors may be encountered.**
- **when simulating LivePremier firmware v2.0.228 and above:**
  - **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
  - **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

### New Feature

- Supports LivePremier firmware v2.5.14

### Evolution

- None

### Bug fixes

- None

<b>Product</b>	LivePremier Simulator
<b>Date</b>	February 22 <sup>nd</sup> , 2022
<b>Version</b>	1.5.1

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Warnings

- **do not use LivePremier Simulator and Midra 4K Simulator simultaneously as erroneous behaviors may be encountered.**
- **when simulating LivePremier firmware v2.0.228 and above:**
  - **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
  - **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

### New Feature

- Supports LivePremier firmware v2.4.27

### Evolution

- None

### Bug fixes

- In the SETUP>Preconfig>Backgrounds page of the Web RCS, assigning a capacity 2 input to a capacity 1 output now reports an error
- In the LIVE>Screens page of the Web RCS, switching Preset Toggle from On to Off doesn't cause Screen Memory Id problems on Preview anymore.

<b>Product</b>	LivePremier Simulator
<b>Date</b>	November 22 <sup>nd</sup> , 2021
<b>Version</b>	1.4.4

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Warnings

- **when simulating LivePremier firmware v2.0.228 and above:**
  - o **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**
- **when simulating LivePremier firmware v2.3.103 and above:**
  - o **do not disable both HTTP and HTTPS servers in the Remote Control settings of the device as it will result in the permanent loss of the session**

### New Feature

- Supports LivePremier firmware v2.3.103
- Support of new hardware:
  - o SDVoE input card (ref. AQL-ACC-IN-SDVOE)
  - o SDVoE output card (ref. AQL-ACC-OUT-SDVOE)
  - o Input filler card (ref.AQL-ACC-IN-FILLER)

### Evolution

- None

### Bug fixes

- A screen without assigned outputs must not appear in the Live page of the Web RCS

<b>Product</b>	LivePremier Simulator
<b>Date</b>	May <sup>th</sup> , 2021
<b>Version</b>	1.3.0

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### **Warning when simulating LivePremier firmware v2.0.228 and above:**

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

### New Feature

- Supports LivePremier firmware v2.2.79

### Evolution

- None

### Bug fixes

- None

<b>Product</b>	LivePremier Simulator
<b>Date</b>	March 23 <sup>rd</sup> , 2021
<b>Version</b>	1.2.7

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Warning when simulating LivePremier firmware v2.0.228 and above:

- if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66

### New Feature

- None

### Evolution

- Add the simulated device a default serial number "ZZ9999" (Useful for AW VideoCompositor for LivePremier and Crestron driver programing)

### Bug fixes

- None

<b>Product</b>	LivePremier Simulator
<b>Date</b>	February 24 <sup>th</sup> , 2021
<b>Version</b>	1.2.6

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### **Warning when simulating LivePremier firmware v2.0.228 and above:**

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

### New Feature

- Supports LivePremier firmware v2.1.82

### Evolution

- Audio management and routing support

### Bug fixes

- When the first input card is a DisplayPort card, the DPH104 feature is not available



<b>Product</b>	LivePremier Simulator
<b>Date</b>	December 15 <sup>th</sup> , 2020
<b>Version</b>	1.2.3

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### **Warning when simulating LivePremier firmware v2.0.228 and above:**

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

### New Feature

- Simulation of LivePremier firmware v2.1.73

### Evolution

- None.

### Bug fixes

- None

<b>Product</b>	LivePremier Simulator
<b>Date</b>	July 30 <sup>th</sup> , 2020
<b>Version</b>	1.1.8

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### **Warning when simulating LivePremier firmware v2.0.228:**

- **if the Basic Authentication feature is enabled without changing the password, the default password is the MAC address 11:22:33:44:55:66**

### New Feature

- Simulation of LivePremier firmware v2.0.228
- Generation of ordering numbers for LivePremier's Aquilon C and C+

### Evolution

- None.

### Bug fixes

- None

<b>Product</b>	LivePremier Simulator
<b>Date</b>	May 18 <sup>th</sup> , 2020
<b>Version</b>	1.0.6

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

---

## Technical Notes:

---

### New Feature

- The LivePremier Simulator is now also available for Mac.

### Evolution

- None.

### Bug fixes

- Working with RC400T can crash the Web RCS server
- Correction on AOI management
- Output capacities may be inconsistent

<b>Product</b>	LivePremier Simulator
<b>Date</b>	April 29 <sup>th</sup> , 2020
<b>Version</b>	1.00.00

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Supported OS

This initial version is only available for Microsoft Windows systems. The Mac OS version will be released later.

### Initial published release

- Support for LivePremier series: Aquilon RS alpha, RS1, RS2, RS3, RS4, C and C+
- Simulation of LivePremier firmware v1.2.10
- Customizable I/O card types
- Up to 10 session slots, one session running at a time
- 2 possible input formats depending on input capacity:
  - o Capacity 1: 1920x 1080
  - o Capacity 2: 3840x 2160
- Import/Export of the device configuration using the Web RCS
- Usable with RC400T